










		insulation class	directly fitted	degree of protection	tension volt	attachment	weight kg.
9068 9066				IP 20	220-240	E27	1.080
9067 9069				IP 20	120	E26 SB CFL max 25W	1.080

diameter Ø height diffuser length min÷max
38 28 40÷232

9038 9035				IP 20	220-240	E27	1.580
9039 9036				IP 20	120	E26 SB CFL max 25W	1.580

diameter Ø height diffuser length min÷max
52 33 46÷241

9097 9095				IP 20	220-240	E27	4.500
9098 9096				IP 20	120	E26 SB CFL max 25W	4.500



diameter Ø height diffuser length min÷max
83 55 70÷260

packaging	quantity	weight kg.	volume m ³	size
9068 / 9069	1	2.140	0.058	42X32X43
9066 / 9067	1	2.140	0.058	42X32X43
9038 / 9039	1	3.260	0.133	55X41X55
9035 / 9036	1	3.440	0.133	55X41X55
9095 / 9096	1	6.500	0.511	86X65X86
9097 / 9098	1	6.500	0.511	86X65X86

9038/9068/9097/9039/9067/9098
Matt opaque

BB/white	
MM/brown	

9035/9066/9095/9036/9069/9096
Metallic

XX/chrome	
GG/gold	
RR/copper	